

单滑板机参数表/SPECIFICATION

项目/DESCRIPTION		单位/UNIT	VS-1200				
射出系统 INJECTION UNIT	螺杆直径	SCREW DIAMETER	mm	φ 36	φ 40	φ 44	φ 48
	射出压力	INJECTION PRESSURE	kg/cm ²	2666	2160	1785	1500
	理论射出容积	THEORETICAL INJECTION VOLUME	cm ³	183	226	274	326
	射出重量 (PS)	INJECTION CAPACITY (PS)	g	173	214	259	308
			oz	6.1	7.5	9.1	10.9
射出率	INJECTION RATE	cm ³ /sec	102	126	152	181	
锁模系统 CLAMPING UNIT	锁模力	CLAMPING FORCE	ton	120			
	模柱间距	SPACE BETWEEN TIE-BARS	mm	620×470			
	上模板尺寸	UPPER PLATEN SIZE	mm	840×690			
	单滑板尺寸	SLIDE TABLE SIZE	mm	600×690			
	单滑板行程	SLIDE STROKE	mm	720			
	最小模厚	MINIMUM MOLD THICKNESS	mm	250(+50)			
	开模行程	OPENING STROKE	mm	300			
	最大开模距	MAXIMUM OPENING DAYLIGHT	mm	550(+50)			
	顶出力	EJECTOR FORCE	ton	4			
	顶出高度	EJECTOR STROKE	mm	70			
其他 OTHERS	系统最大压力	HYDAULIC SYSTEM PRESSURE	kg/cm ²	160			
	伺服泵浦流量	MAXIMUM PUMP FLOW	L/min	120			
	油箱容积	OIL TANK VOLUME	L	400			
	冷却水用量	COOLING WATER CAPACITY	L/min	100			
	电热容量	HEATER CAPACITY	kW	12.9	14.9	15.9	17.9
	机器尺寸	MACHINE SIZE (L×W×H _{min})	mm	3.5×1.5×3.2			
	机器重量	MACHINE WEIGHT (APPROX.)	t	5.5			