

转盘机参数表/SPECIFICATION

项目/DESCRIPTION		单位/UNIT	VR-1600				
射出系统 INJECTION UNIT	螺杆直径	SCREW DIAMETER	mm	φ 40	φ 44	φ 48	φ 52
	射出压力	INJECTION PRESSURE	kg/cm ²	2660	2198	1847	1573
	理论射出容积	THEORETICAL INJECTION VOLUME	cm ³	251	304	362	425
	射出重量 (PS)	INJECTION CAPACITY (PS)	g	237	287	342	402
			oz	8.4	10.1	12.1	14.2
射出率	INJECTION RATE	cm ³ /sec	126	152	181	212	
锁模系统 CLAMPING UNIT	锁模力	CLAMPING FORCE	ton	160			
	上模板尺寸	UPPER PLATEN SIZE	mm	1680×630			
	圆盘尺寸	SHUTTLE TABLE SIZE	mm	1400			
	容模尺寸	MOLD SIZE (APPROX.)	mm	横向: 600×500			
				纵向: 540×540			
	最小模厚	MINIMUM MOLD THICKNESS	mm	250 (+50)			
	开模行程	OPENING STROKE	mm	300			
	最大开模距	MAXIMUM OPENING DAYLIGHT	mm	550 (+50)			
	顶出力	EJECTOR FORCE	ton	4			
顶出高度	EJECTOR STROKE	mm	70				
其他 OTHERS	系统最大压力	HYDAULIC SYSTEM PRESSURE	kg/cm ²	160			
	伺服泵浦流量	MAXIMUM PUMP FLOW	L/min	150			
	油箱容积	OIL TANK VOLUME	L	500			
	冷却水用量	COOLING WATER CAPACITY	L/min	100			
	电热容量	HEATER CAPACITY	kW	14.9	15.9	17.9	20.2
	机器尺寸	MACHINE SIZE (L×W×H _{min})	mm	3.0×2.2×3.9			
	机器重量	MACHINE WEIGHT (APPROX.)	t	7.2			