

转盘机参数表/SPECIFICATION

项目/DESCRIPTION		单位/UNIT	VR-2000				
射出系统 INJECTION UNIT	螺杆直径	SCREW DIAMETER	mm	φ 44	φ 48	φ 52	φ 56
	射出压力	INJECTION PRESSURE	kg/cm <sup>2</sup>	2644	2222	1893	1632
	理论射出容积	THEORETICAL INJECTION VOLUME	cm <sup>3</sup>	334	398	467	542
	射出重量 (PS)	INJECTION CAPACITY (PS)	g	316	376	441	512
			oz	11.1	13.3	15.6	18.1
射出率	INJECTION RATE	cm <sup>3</sup> /sec	152	181	212	246	
锁模系统 CLAMPING UNIT	锁模力	CLAMPING FORCE	ton	200			
	上模板尺寸	UPPER PLATEN SIZE	mm	1930×730			
	圆盘尺寸	SHUTTLE TABLE SIZE	mm	1600			
	容模尺寸	MOLD SIZE (APPROX.)	mm	横向: 700×600			
				纵向: 630×630			
	最小模厚	MINIMUM MOLD THICKNESS	mm	350			
	开模行程	OPENING STROKE	mm	450			
	最大开模距	MAXIMUM OPENING DAYLIGHT	mm	800			
	顶出力	EJECTOR FORCE	ton	7			
顶出高度	EJECTOR STROKE	mm	100				
其他 OTHERS	系统最大压力	HYDAULIC SYSTEM PRESSURE	kg/cm <sup>2</sup>	160			
	伺服泵浦流量	MAXIMUM PUMP FLOW	L/min	184			
	油箱容积	OIL TANK VOLUME	L	600			
	冷却水用量	COOLING WATER CAPACITY	L/min	100			
	电热容量	HEATER CAPACITY	kW	15.9	17.9	20.2	23.5
	机器尺寸	MACHINE SIZE (L×W×H <sub>min</sub> )	mm	3.8×2.8×3.5			
	机器重量	MACHINE WEIGHT (APPROX.)	t	10			