

转盘机参数表/SPECIFICATION

项目/DESCRIPTION		单位/UNIT	VR-600				
射出系统 INJECTION UNIT	螺杆直径	SCREW DIAMETER	mm	φ 28	φ 32	φ 36	φ 42
	射出压力	INJECTION PRESSURE	kg/cm <sup>2</sup>	2678	2050	1620	1190
	理论射出容积	THEORETICAL INJECTION VOLUME	cm <sup>3</sup>	86	113	142	194
	射出重量 (PS)	INJECTION CAPACITY (PS)	g	81	107	134	183
			oz	2.9	3.8	4.7	6.5
射出率	INJECTION RATE	cm <sup>3</sup> /sec	62	80	102	138	
锁模系统 CLAMPING UNIT	锁模力	CLAMPING FORCE	ton	60			
	上模板尺寸	UPPER PLATEN SIZE	mm	620×550			
	圆盘尺寸	SHUTTLE TABLE SIZE	mm	900			
	容模尺寸	MOLD SIZE (APPROX.)	mm	横向: 400×300			
				纵向: 300×350			
	最小模厚	MINIMUM MOLD THICKNESS	mm	200(+50)			
	开模行程	OPENING STROKE	mm	250			
	最大开模距	MAXIMUM OPENING DAYLIGHT	mm	450(+50)			
	顶出力	EJECTOR FORCE	ton	2			
顶出高度	EJECTOR STROKE	mm	50				
其他 OTHERS	系统最大压力	HYDAULIC SYSTEM PRESSURE	kg/cm <sup>2</sup>	140			
	伺服泵浦流量	MAXIMUM PUMP FLOW	L/min	78			
	油箱容积	OIL TANK VOLUME	L	300			
	冷却水用量	COOLING WATER CAPACITY	L/min	60			
	电热容量	HEATER CAPACITY	kW	5.8			
	机器尺寸	MACHINE SIZE (L×W×H <sub>min</sub> )	mm	2.3×1.6×3.0			
	机器重量	MACHINE WEIGHT (APPROX.)	t	3.0			